



PA6G Rundstäbe – Standardabmessungen

Stärke, mm		Länge x Breite, mm
Wert	Toleranz	
40,0	0~+ 5 mm	1.000 (0/+40)
45,0	0~+ 5 mm	
50,0	0~+ 5 mm	
60,0	0~+ 5 mm	
65,0	0~+ 5 mm	
70,0	0~+ 5 mm	
75,0	0~+ 5 mm	
80,0	0~+ 5 mm	
85,0	0~+ 5 mm	
90,0	0~+ 5 mm	
100,0	0~+ 5 mm	
110,0	0~+ 5 mm	
120,0	0~+ 5 mm	
130,0	0~+ 5 mm	
140,0	0~+ 5 mm	
150,0	0~+ 4 mm	
160,0	0~+ 4 mm	
170,0	0~+ 4 mm	
180,0	0~+ 4 mm	
190,0	0~+ 4 mm	
200,0	0~+ 4 mm	
210,0	0~+ 3 mm	
220,0	0~+ 3 mm	
230,0	0~+ 3 mm	
240,0	0~+ 3 mm	
250,0	0~+ 3 mm	
260,0	0~+ 3 mm	
270,0	0~+ 3 mm	
280,0	0~+ 3 mm	
290,0	0~+ 3 mm	
300,0	0~+ 3 mm	

Zwischenstärken sowie kleinere und größere auf Anfrage